



P171539

HYDRAULIC FILTER, CARTRIDGE

Attributes

Outer Diameter	95 mm (3.74 inch)
Inner Diameter	41 mm (1.61 inch)
Length	202 mm (7.95 inch)
Gasket OD	46.6 mm (1.83 inch)
Gasket ID	39.6 mm (1.56 inch)
Overall Length	209 mm (8.23 inch)
Efficiency Beta 2	10 micron
Efficiency Beta 200	32 micron
Efficiency Beta 1000	36 micron
Efficiency Test Std	ISO 16889
Bypass Valve	Yes

Bypass Valve Setting LR	1.5 bar (22 psi)
Collapse Burst	10 bar (145 psi)
Maximum Operating Temperature	120 °C (248 °F)
Style	Cartridge
Series	FIK
Media Type	Cellulose
Primary Application	F.B.O. CR180

Packaged Dimensions

Packaged Length	0.10920984 M
Packaged Width	0.09906 M
Packaged Height	0.24893016M
Packaged Weight	0.4921477214 KG
Packaged Volume	0.0026929321 M3

Other Information

Country of Origin	Italy
NMFC Code	069100-03
HTS Code	8421298090
UPC Code	742330083758

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.